



Positioners & Holders

830-0001

RING HOLDERS FOR NONLINEAR CRYSTALS




830-0001-10



830-0001-06



- Black anodized aluminium body
- Teflon or white anodized aluminium adapter for particular crystal size
- Easy assembling and disassembling

Ring mounts made from black anodized aluminum and Teflon or white anodized aluminium adapter are available for safe and convenient handling of nonlinear crystals. The crystals are glued into white anodized aluminium adapter (830-0001-06). No glue is used for fixation of the crystal into open ring holder with teflon adapter. The standard sizes are Ø25.4 or Ø30 mm and thickness – 6, 10.5, 13.5 or 17.5 mm depending on crystal size.



* C.A. - depends on crystal aperture

830-0001-10



830-0001-06

Please indicate the exact crystal size when ordering.

Part No	Diameter, mm	Thickness, mm	Max. acceptable crystal size, mm	Price, EUR
830-0001-06	25.4	6	12×12×0.5	50
830-0001-10	25.4	10.5	12×12×3	50
830-0001-13	25.4	13.5	12×12×6	50
830-0001-17	25.4	17.5	12×12×15	90
830-0002-10	30	10.5	15×15×3	50
830-0002-13	30	13.5	15×15×6	50
830-0002-17	30	17.5	15×15×15	90

HOUSING ACCESSORIES

Positioning Mount
840-0199 for
Nonlinear
Crystal Housing
See page 2.26

